



Low Output Flexible LED Strip Light

EL-9FLX

UL # E348280
 Spool Length: 16.4 ft
 Weight: 0.2 oz.
 Width: 0.3 in.
 Depth: 0.1 in.
 LED Spacing: 1.3 in. (between centers)
 Cuttable: every 3 LEDs / 4 in.
 Max. Length of run: 16.4 ft.
 Fixture Surface Temp. 68° - 104° F
 UV/IR Radiation: None
 Lifespan: 50,000 hours



The Low Output LED Strip Light, available by the foot in a custom length, is the perfect fixture for those in need of a low output, low light strip installation. This LED strip is exactly half the brightness and half the power consumption of our standard Flexible LED Strip Light. This LED tape comes with a 3M adhesive backing which allows easy mounting virtually anywhere. This flat LED strip emits light in all directions with a 140 degree light beam angle.

The low profile of our LED ribbons allow for use in many discreet locations and applications. The flexible design and efficiency of Low Output Strip Lighting make it ideal for lighting:

- Marker lighting
- Theaters and cinemas
- Pathways and walkways
- Ambient lighting
- Interior cove lighting
- Stairs, steps, and railings

Low energy consumption not only means saving money, it also can translate to an elimination of electrical shock and fire danger. This solid state Light Strip lasts for 50,000 hours which is 8 years if left constantly on. This strip will cost \$.90 per foot if left on all year. LEDs are durable, small, and very efficient. As all of Elemental products, our Flexible LED Light holds the prestigious ROHS certificate, which ensures that no environmentally harmful components were used in manufacturing.

Elemental LED fully controls all technical aspects of manufacturing which means if you are looking for a different style, whether in Brightness, Voltage or Color, we can customize! If your company has a special project or specific needs, please contact our support team at 877.564.5051.



color	color temp.	voltage	lumens / ft.	IP Rating	beam angle	type of led	power consumption / ft.	cri	# of leds / ft.
warm white	3000k	12V DC	35	40	140°	3528 SMD	0.72W / 60mA	70-75	9
neutral white	6000k	12V DC	39	40	140°	3528 SMD	0.72W / 60mA	75-80	9