


STREAMLITE™ DIFFUSED LINEAR LIGHT

Dot-free linear lighting without any visible LEDs. Ideal for tight spaces and simple, impactful installations.



24
VDC

90+
CRI

TITLE
24

FEATURES & BENEFITS

- Uniform, diffused light appears dotless even without a diffusing lens
- Very small size, ideal for tight spaces
- 180° beam angle for even light distribution
- Compatible with channels and other popular accessories

QUICK SPECS

Voltage	24VDC
Width	8mm
CRI	90+
Warranty	7-Year Limited Warranty
Dimming	Dimmable
Environment	Indoor / Damp Location (IP20)
Certification	UL Listed 2108
Connector	8mm Terminal Block

Visit the product page on the website for specification sheets, install guides, IES files, and photometric reports.

DI	VOLTAGE	MODEL	CCT	LENGTH
DI	24V (24VDC)	STMLT	27 (2700K) 40 (4000K)	016 (16.4 ft.)
		STMLT4	30 (3000K) GN (Green) 35 (3500K) RD (Red)	100 (100 ft.)

EXAMPLE: 24V STREAMLITE™ 2700K 16.4 FT. SPOOL = DI-24V-STMLT-27-016

24VDC		
	STMLT	STMLT4
	Max. Run: 20 ft. Cut Points: 1.8 in. Wattage: 3.3 W/ft.	Max. Run: 16.4 ft. Cut Points: 1.8 in. Wattage: 5.0 W/ft.
CCT	Lumens / ft.	Lumens / ft.
2700K	288	402
3000K	292	409
3500K	285	421
4000K	323	466
Green	236	—
Red	42	—